


DECLARATION OF PERFORMANCE

0338/CPR/1013/414/EWB

<p>1. Unique identification code of the product type:</p> <p>Ecworx® Nylon Pile Broadloom Carpet Face weight 508 to 1356 gm/sq. metre (18 to 40 oz./sq.yd.)</p>																	
<p>2. Type, batch or serial number or other element allowing identification of the product as required pursuant to Article 11(4):</p> <p>Broadloom carpet. For pattern name and style number please refer to packaging and/or invoice.</p>																	
<p>3. Intended use or uses of the product in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p> <p>For use as an indoor floor covering as specified by the manufacturer.</p>																	
<p>4. Name and contact address of the manufacturer as required pursuant to Article 11(5):</p> <p>Shaw Industries Group Inc., PO Drawer 2128, 616E Walnut Avenue, Dalton, Georgia 30722 USA</p>																	
<p>5. Where applicable, name and contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)</p> <p>Not applicable</p>																	
<p>6. System of assessment and verification of constancy of performance of the product as set out in Annex V:</p> <p>System 1</p>																	
<p>7. Name of the notified test laboratory that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).</p> <p>BTTG, Notified Laboratory 0338 – CPR - 1013</p>																	
<p>8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued</p> <p>Not applicable</p>																	
<p>9. Declared Performance:</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 33%;">Essential characteristics</th> <th style="width: 33%;">Performance</th> <th style="width: 33%;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Reaction to Fire</td> <td>Cfl-s1</td> <td>EN14041:2004/AC:2006</td> </tr> <tr> <td>Formaldehyde Emissions</td> <td>EI</td> <td>EN14041:2004/AC:2006</td> </tr> <tr> <td>Slip Resistance</td> <td>DS</td> <td>EN14041:2004/AC:2006</td> </tr> <tr> <td>Electrical Behaviour (antistatic)</td> <td><2Kv</td> <td>EN14041:2004/AC:2006</td> </tr> </tbody> </table>			Essential characteristics	Performance	Harmonised technical specification	Reaction to Fire	Cfl-s1	EN14041:2004/AC:2006	Formaldehyde Emissions	EI	EN14041:2004/AC:2006	Slip Resistance	DS	EN14041:2004/AC:2006	Electrical Behaviour (antistatic)	<2Kv	EN14041:2004/AC:2006
Essential characteristics	Performance	Harmonised technical specification															
Reaction to Fire	Cfl-s1	EN14041:2004/AC:2006															
Formaldehyde Emissions	EI	EN14041:2004/AC:2006															
Slip Resistance	DS	EN14041:2004/AC:2006															
Electrical Behaviour (antistatic)	<2Kv	EN14041:2004/AC:2006															
<p>10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p> <p>Signed for and behalf of the manufacturer by:</p> <p style="text-align: center;"></p> <p>James Slaughter, Director of Quality Systems. Dalton, Ga., USA July 2013</p>																	