DECLARATION OF PERFORMANCE

0338/CPR/1013/414/RBL

1. Unique identification code of the product type:

Classicbac® and SoftBac® Nylon Pile Broadloom Carpet - Residential
Face weight : 339 to 3390 gm/sq mtr (10 oz to 100 oz per sq/yd)

2. Type, batch or serial number or other element allowing identification of the product as required pursuant to Article 11(4):

Broadloom carpet. For pattern name and style number please refer to packaging and/or invoice.

3. Intended use or uses of the product in accordance with the applicable harmonised technical specification , as foreseen by the manufacturer:

For use as an indoor floor covering as specified by the manufacturer.

4. Name and contact address of the manufacturer as required pursuant to Article 11(5):

Shaw Industries Group Inc., PO Drawer 2128, 616E Walnut Avenue, Dalton, Georgia 30722 USA

5. Where applicable, name and contact address of the authorised representative whose mandate covers tasks specified in Article 12(2)
Not applicable

6. System of assessment and verification of constancy of performance of the product as set out in Annex V:

EN14041:2004/AC:2006 4.1.4 Table 2 : - Classes of reaction to fire for textile floor coverings classified without further testing. 100% polyamide pile.

7. Name of the notified test laboratory that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).
Not applicable

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issue
Not applicable

9. Declared Performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	**Efl**	**EN14041:2004/AC:2006**
Slip Resistance	**DS**	**EN14041:2004/AC:2006**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

James Slaughter, Director of Quality Systems. **Dalton, Ga., USA** **October 2013**