(		ATION OF PERFO	RMANCE Januar Halitiad	
1.	Unique identification code of the product-type:			
LL-DoP-002				
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):			
	FREELINE / SIMPLAY Loose Lay Flooring Tile (EN ISO 10582)			
3.	Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:			
	For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.			
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):			
	James Halstead PLC, Beechfield, Hollinhurst Road, Radcliffe, Manchester, M26 1JN, United Kingdom			
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):			
	not applicable			
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3			
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).			
	British Textile Technology Group (BTTG) Wira House, West Park Road, Leeds, LS16 6QL		not applicable	
8.	Notified Body No 338 In case of the declaration of performance concerning a const	ruction product for which a European Technical A	certificate of constancy of performance	
0.	not applicable			
9.	Declared performance			
	Essential characteristics	Performance	Harmonised technical specification	
	Reaction to fire		EN 14041: 2004/AC:2006	
	Content of Pentachlorophenol	Ê DL PCP	EN 14041: 2004/AC:2006	
	Formaldehyd Emissions	° NA HCHO	EN 14041: 2004/AC:2006	
	Slip resistance	S S S S S S S S S S S S S S S S S S S	EN 14041: 2004/AC:2006	
	Electrical behavior (dissipative)	NPD	EN 14041: 2004/AC:2006	
	Electrical behavior (conductive)	NPD	EN 14041: 2004/AC:2006	
	Electrical behavior (antistatic)	NPD	EN 14041: 2004/AC:2006	
	Thermal conductivity [W/mK]	0.0226 m <sup>2</sup> K/W	EN 14041: 2004/AC:2006	
	Water-tightness	NPD	EN 14041: 2004/AC:2006	
10.	The performance of the product identified in points 1 and 2 is This declaration of performance is issued under the sole resp Signed for and on behalf of the manufacturer by:		oint 9.	
	Mr Steve Mulholland, Group Technical Manager			
	(name and function)		S Mulholland	
	25th June 2013, Manchester, UK (place and date of issue)		(signature)	